

SEE CALTRANS
DETAILS A88A, A88B,
A90A, AND A90B

NOTES:

1. LOCATE RAMP AT MIDPOINT OF CURB RETURNS.
2. SIDEWALK AND RAMP SHALL BE CONSTRUCTED WITH MINOR CONCRETE IN ACCORDANCE WITH CALTRANS STANDARD SPECIFICATIONS.
3. NO PULL BOX, UTILITY VAULT, UTILITY POLE, MANHOLE OR OTHER OBSTRUCTIONS SHALL BE LOCATED WITHIN SIDEWALK OR RAMP AREA (RETURN TO RETURN).
4. ALL INLETS SHALL BE LOCATED OUTSIDE OF CURB RETURNS.
5. CONTRACTOR TO PROVIDE ADEQUATE JOINTS TO CONTROL CRACKING.
6. MEET CURRENT ADA STANDARDS. INSTALL RAISED TRUNCATED DOMES AS REQUIRED.
7. DOWEL RAMP ONLY INTO CURB/GUTTER WITH #4 REBAR 18" O.C. 6" INTO CURB.

YUBA COUNTY DEPARTMENT OF PUBLIC WORKS	
WHEEL CHAIR RAMP	
APPROVED BY: <i>Donald Peters</i>	DATE: 8/11/22
	203