


URBAN INDUSTRIAL/COMMERCIAL ROAD



NOTES:

1. REFER TO SECTION 6 OF YUBA COUNTY STANDARD SPECIFICATIONS FOR ADDITIONAL REQUIREMENTS.
2. SOIL STABILIZATION SECTION, A.B. LAYER AND A.C. LAYER SHALL BE COMPACTED TO 95% RELATIVE COMPACTION.
3. RAISED MEDIAN TO BE DETERMINED BY PUBLIC WORKS. SEE STANDARD MEDIAN DETAIL IF A RAISED MEDIAN IS SPECIFIED.
4. DESIGN SPEED OF 40 MPH OR AS APPROVED BY PUBLIC WORKS.
5. SOIL STABILIZATION TREATMENT IS REQUIRED ON ALL SUBGRADE WHEN R-VALUE IS 20 OR LESS AND/OR AS RECOMMENDED BY THE GEOTECHNICAL ENGINEER AND AS DIRECTED BY PUBLIC WORKS.
6. IF SOIL STABILIZATION IS REQUIRED, EXTEND TO BACK OF WALK FOR ATTACHED SIDEWALK.
7. 20 TON MIN. PROOF ROLL REQUIRED ON SUBGRADE AND AGGREGATE BASE PRIOR TO PAVING.

YUBA COUNTY DEPARTMENT OF PUBLIC WORKS	
URBAN INDUSTRIAL/COMMERCIAL	
APPROVED BY: <i>Daniel J. King</i>	DATE: 8/11/22
104	